

swapping/electric vehicle batteries

Electric vehicle lithium battery energy saving, green, environmental protection, low carbon "performance strong" use is also relatively light, fast.



▲ This picture is for reference only



GPS/ Beidou positioning system



Light weight, Small size



Long cycle life



Scan the code to change the battery, and start sailing in 10 seconds



Smart BMS



In the extreme performance safety test, the battery will not catch fire, explode, leak, and be safer to use.

Suitable for the crowd

- Swapping battery for express delivery
- Swapping battery for take-out delivery
- Batteries of electric motorcycle for community residents traveling

Item	Charging Battery	Switching Battery
Charging time	6-10H	5S
Endurance mileage	40Km	Unlimited
Weight	30kg	6kg
Battery Life	1-2Year	Unlimited

Model	Nominal voltage	Rated capacity	Size	Weight	Cycle life	Charging cut-off voltage	Discharging cut-off voltage	Operating temperature	Storage temperature
Vehicle battery									
4820	51.2V	20Ah	235x155x166mm	12kg	3000	58.4V	40V	-20°C~60°C	-20°C~25°C
4830	51.2V	30Ah	290x200x170mm	14kg	3000	58.4V	40V	-20°C~60°C	-20°C~25°C
4860	51.2V	60Ah	590x220x195mm	30kg	3000	58.4V	40V	-20°C~60°C	-20°C~25°C
6020	64V	20Ah	235x185x170mm	14kg	3000	73V	50V	-20°C~60°C	-20°C~25°C
6030	64V	30Ah	195x190x325mm	18kg	3000	73V	50V	-20°C~60°C	-20°C~25°C
6050	64V	50Ah	380x285x190mm	29.5kg	3000	73V	50V	-20°C~60°C	-20°C~25°C
7220	76.8V	20Ah	184x162x279mm	14kg	3000	87.6V	60V	-20°C~60°C	-20°C~25°C
7230	76.8V	30Ah	430x220x160mm	26kg	3000	87.6V	60V	-20°C~60°C	-20°C~25°C
7250	76.8V	50Ah	285x445x187mm	35kg	3000	87.6V	60V	-20°C~60°C	-20°C~25°C
Swapping									
4820	51.2V	20Ah	290x175x145mm	10KG	1200	58.4V	40V	-20°C~60°C	-20°C~25°C
4825	51.2V	25Ah	290x175x145mm	10.5KG	1200	58.4V	40V	-20°C~60°C	-20°C~25°C
4830	51.2V	30Ah	300x180x170mm	13KG	1200	58.4V	40V	-20°C~60°C	-20°C~25°C
6020	64V	20Ah	290x175x145mm	12KG	1200	73V	50V	-20°C~60°C	-20°C~25°C
6030	64V	30Ah	320x180x170mm	15KG	1200	73V	50V	-20°C~60°C	-20°C~25°C